


ALUMINUM CLAD SWING PATIO DOOR SIZING AND TECHNICAL DETAILS

ALUMINUM CLAD SWING PATIO DOOR door types



Sidelite/ Stationary

A fixed panel used to allow additional light into a home.

(No Screen)




Single Swing

A single active door panel that can swings into a home left or right. (Outswing and Retractable Screen Optional)



2P-Single Swing

A single swing door with one stationary panel on either side of it. (Sliding Screen Standard)



3P-Single Swing

A single swing door with two stationary panels on either side of it or one stationary panel on each side.

(Sliding Screen Standard)



French Swing


Double panel door with one active and a secondary active panel to open the door fully. (Outswing and Retractable Screens Optional)

custom sizes & combinations

Patio doors are available in any size within a 1/16" of an inch between our minimum and maximum dimensions. Additionally, patio door units can be mulled with other doors, transoms, or stationary panels to fill an opening or allow more light into a home.

handing

Swing patio door handings (which side the door opens from) are as shown below. All doors are inswing (swing into the room). Outswing doors available with special quotation.




standard size widths

Select from the different widths and door types show below.

Casco Callout	Width	Туре	Unit Dimension - Width	Egress Width
CSWS10XX	1/0	Sidelite	1' 1-9/16" (13-9/16")	N/A
CSWS12XX	1/2	Sidelite	1' 3-9/16" (15-9/16")	N/A
CSWS14XX	1/4	Sidelite	1' 5-9/16" (17-9/16")	N/A
CSWS18XX	1/8	Sidelite	1' 9-9/16" (21-9/16")	N/A
CSW20XX	2/0	Single Swing or Stationary	1' 11-7/8" (23-7/8")	19-9/16"
CSW26XX	2/6	Single Swing or Stationary	2' 5-7/8" (29-7/8")	25-9/16"
CSW28XX	2/8	Single Swing or Stationary	2' 7-7/8" (31-7/8")	27-9/16"
CSW30XX	3/0	Single Swing or Stationary	2' 11-7/8" (35-7/8")	31-9/16"
CSW33XX	3/3	Single Swing or Stationary	3' 2-7/8" (38-7/8")	34-9/16'
CSW40XX	4/0	2P-Single Swing	3' 10-7/8" (46-7/8")	19-9/16"
CSW50XX	5/0	2P-Single Swing	4' 10-7/8" (58-7/8")	25-9/16"
CSW54XX	5/4	2P-Single Swing	5' 2-7/8" (62-7/8")	27-9/16'
CSW60XX	6/0	2P-Single Swing	5' 10-7/8" (70-7/8")	31-9/16'
CSW66XX	6/6	2P-Single Swing	6' 4-7/8" (76-7/8")	34-9/16'
CSW76XX	7/6	3P-Single Swing	7' 3-7/8" (87-7/8")	25-9/16'
CSW80XX	8/0	3P-Single Swing	7' 9-7/8" (93-7/8")	27-9/16'
CSW90XX	9/0	3P-Single Swing	8' 9-7/8" (105-7/8")	31-9/16'
CSW99XX	9/9	3P-Single Swing	9' 6-7/8" (114-7/8")	34-9/16'
CSWF40XX	4/0	French	3' 10-7/8" (46-7/8")	40-3/4'
CSWF50XX	5/0	French	4' 10-7/8" (58-7/8")	52-3/4'
CSWF54XX	5/4	French	5' 2-7/8" (62-7/8")	56-3/4'
CSWF60XX	6/0	French	5' 10-7/8" (70-7/8")	64-3/4
CSWF66XX	6/6	French	6' 4-7/8" (76-7/8")	70-3/4"
Replace the "XX" in each callout number with the required call out height numbers.				

GRILLE DESIGN STYLES





light opening

One Panel: Unit Width - 10.32" = Light Width
Two Panel: Unit Width - 20.25" = Total Light Width
Three Panel: Unit Width - 30.82" = Total Light Width
Unit Height - 15.32" = Light Height

measurement guide

A reference guide on how to measure for new patio doors is available on Casco's website: www.cascoonline.com/measure

unit numbers Call Out Width

Door Type Call O

standard size heights

6/9 RO Height

Unit Dimension Height: 6' 8-3/16 (80-3/16")
Call Out Height: (69)

7/0 RO Height

Unit Dimension Height: 6' 11-11/16" (83-11/16") Call Out Height: (70)

6/11 RO Height

Unit Dimension Height: 6' 10-3/16" (82-3/16") Call Out Height: (611)

8/0 RO Height

Unit Dimension Height: 7' 11-3/16" (95-3/16")
Call Out Height: (80)

NOTE: ADA, low profile, sill available. Deduct 5/8" from height.

rough opening

Rough Opening Width: Add 5/8" to Unit Dimension Width Rough Opening Height: Add 13/16" to Unit Dimension Height

* Meet or exceed a clear opening of 5.7 sq.ft. with a clear opening width of 20" and a clear opening height of 24".